

PAT-NO: JP361171151A
 DOCUMENT-IDENTIFIER: JP 61171151 A
 TITLE: MANUFACTURE OF MULTILAYERED
 PUBLN-DATE: August 1, 1986

INVENTOR-INFORMATION:

NAME	COUNTRY
KIKUCHI, MASAHIRO	
OKANO, SADA0	
MOCHIZUKI, YASUHIRO	
HIRAO, MITSURU	
NAKAYAMA, YASUSHI	

ASSIGNEE-INFORMATION:

NAME	COUNTRY
HITACHI LTD	N/A
HITACHI HARAMACHI SEMICONDUCTOR LTD	N/A

APPL-NO: JP60010924
 APPL-DATE: January 25, 1985

INT-CL (IPC): H01L021/88





US-CL-CURRENT: 438/FOR.355

ABSTRACT:

PURPOSE: To contrive to improve the adhesion of the upper wiring layer by reducing the height of the columnar part of a through-hole aperture, by a method wherein the second insulation film is formed taperingly; then, a through-hole having steps is formed in the first insulation film by anisotropic dry etching.

CONSTITUTION: An Si dioxide film 2, the first layer wiring 3, and a thermosetting resin film 4 are formed on a semiconductor substrate 1. A hole 7 for through-hole formation is formed via inorganic insulation film 5 and resist 6, and a tapered hole 8 is formed by isotropic wet etching. Next, the insulation film 4 is anisotropically dry -etched; at this time, the resist pattern 6 is etched and disappears on account of the use of oxygen gas. Besides, because of strong anisotropy, etching vertically advances into a shape like a hole 9. Further, when a reactive ion etching with oxygen is used with the mask of the insulation film 5. The insulation film 4 is vertically etched into a through-hole 10 having steps.

多層配線の製
 第1図の如く
 る。
 第1層配線。
 絶縁膜。
 士 小川勝男



第 2 図

